



CARGO MATE

STEEL FLAT FRONT BUMPER PULL CARGO TRAILERS.

AVAILABLE SIZES

- 12' x 6' x 6'6" w/ 2-3500# axles, 15" tires & 5-hole wheels
- 12' x 6'8" x 6'6" w/ 2-3500# axles, 15" tires & 5-hole wheels
- 14' x 6'8" x 6'6" w/ 2-5200# axles, 15" tires & 6-hole wheels
- 16' x 6'8" x 6'6" w/ 2-5200# axles, 15" tires & 6-hole wheels
- 18' x 6'8" x 6'6" w/ 2-5200# axles, 15" tires & 6-hole wheels
- 20' x 6'8" x 6'6" w/ 2-5200# axles, 15" tires & 6-hole wheels
- 14' x 7'10" x 6'6" w/ 2-5200# axles, 15" tires & 6-hole wheels
- 16' x 7'10" x 6'6" w/ 2-5200# axles, 15" tires & 6-hole wheels
- 18' x 7'10" x 6'6" w/ 2-5200# axles, 15" tires & 6-hole wheels
- 20' x 7'10" x 6'6" w/ 2-5200# axles, 15" tires & 6-hole wheels

DIMENSIONS

- 39" tongue length
- 6', 6' 8" or 7' 10" Width
- 6' or 6'6" Tall

UNDERCARRIAGE

- Rubber torsion axles w/ four-wheel independent suspension & greasable hubs
- Forward self adjusting electric brakes on all wheels
- Radial tires on silver modular wheels w/ chrome center caps
- Spare tire rack on front interior

COUPLER & JACKS

- 2" bulldog coupler & safety chains w/ hooks (standard on 6' widths 10'-14')

- 2-5/16" bulldog coupler & safety chains w/ hooks (standard on 6' widths 16'-20', 6'-8" widths 16'-20', & 7'-10" widths 14'-20')
- Emergency breakaway system: switch, cable & battery box complete w/ battery & charger
- 7K Top-wind jack w/ sand plate

LIGHTS & ELECTRICAL

- DOT required lighting

DESIGN FEATURES

- All steel tubular frame, 2"x4" 3/16" tube steel frame tounge (6' & 6'8") 2"x5" tube steel frame tounge (7'10")
- **Main frame:** 1 1/2" x 3" 14 gauge frame (12'x6' to 16'x6'8") 2"x3" 3/16" wall tubing (18' x 6'8" to 6'8" x 20' and all 7'10" widths)
- **Wall uprights:** 12'x6' to 20'x6'8", 1 1/4" x1 1/4" 14 gauge 7'10" Model 1 1/2" x 1 1/2" 14 gauge on 2" Centers
- **Roof** 1"x1" 16 gauge Roof bows 6x6'8" Wide 24" Center 7'10" on 16" Centers
- **Floor:** 2x2 3/16 Angle Crossmembers 6x6'8" 2x3" 3/16" Angle on 7'10"
- Low profile 6" radius galvneal roof
- Chrome trim w/ colored vinyl insert
- Pin striping
- Flat front w/ 6" radius corners
- Aluminum tread plate gravel guard on front & fenders

- 16 gauge galvneal steel on exterior walls
- 20 gauge galvneal roof
- 3/4" exterior plywood floor
- Tag bracket
- Automotive grade 12 step paint process

CARGO AREA EQUIPMENT

- 32" side access door on curb side w/ one-half bar latch
- 1 1/2"x1/4" inside tie rail on both walls and front
- Double rear door w/ cam latch & hold back

CM Trailers reserves the right to make any change in paint, design, or construction as necessary for engineering. All visual representation, specification, and dimensions are based on the latest product information available at the time of publication. Some of the equipment shown or described is available at extra cost. At no time will any of the material or information contained in this publication have any justifications for resolving disputes. All axle ratings will be listed as per FMVSS 120, Section 5.1 states, the maximum load rating of the tires and rims fitted to an axle shall not be less than the GAWR specified on the certification label.