



CARGO METRO

STEEL GOOSENECK CARGO TRAILER.



AVAILABLE SIZES

- 16' x 7'10" x 6'6" w/ 2-5200# axles, 15" tires & 6-hole wheels
- 18' x 7'10" x 6'6" w/ 2-5200# axles, 15" tires & 6-hole wheels
- 20' x 7'10" x 6'6" w/ 2-7000# axles, 16" tires & 8-hole wheels
- 22' x 7'10" x 6'6" w/ 2-7000# axles, 16" tires & 8-hole wheels
- 24' x 7'10" x 6'6" w/ 2-7000# axles, 16" tires & 8-hole wheels
- 26' x 7'10" x 6'6" w/ 2-7000# axles, 16" tires & 8-hole wheels
- 30' x 7'10" x 6'6" w/ 2-7000# axles, 16" tires & 8-hole wheels

DIMENSIONS

- 7' gooseneck length
- 7'10" width
- 6'6" standard height

UNDERCARRIAGE

- Rubber torsion axles w/ four-wheel independent suspension & greasable hubs
- Forward self adjusting electric brakes on all wheels
- Radial tires on silver modular wheels w/ chrome center caps
- Spare tire rack under gooseneck

COUPLER & JACKS

- Adjustable hitch stem w/ 2-5/16" coupler & safety chains w/ hooks
- Emergency breakaway system: switch, cable & battery box complete w/ battery

LIGHTS & ELECTRICAL

- DOT required lighting & charger
- 12K Single speed drop-leg jack w/handle

DESIGN FEATURES

- Heavy duty low profile gooseneck structure
- All steel 2"x6" tubular frame
- **Mainframe:** 2"x3 3/16" tubular mainframe
- **Wall:** 1 1/2" x 1 1/2" tube steel uprights 24" o.c.
- **Roof:** 1x1 16 gauge tube 16" center
- **Floor:** 2' x 3' x 3/16" Angle Iron 16" centers
- Low profile 6" radius galvaneal roof
- Chrome trim w/ colored vinyl insert
- Pin striping
- Full covered gooseneck nose w/ 6" radius corners
- 3/4" exterior plywood floor
- Tag bracket
- Galvneal Steel 16 gauge side panels
- 20 gauge galvneal steel roof
- Automotive grade 12 step paint process

CARGO AREA EQUIPMENT

- 36" side access door on curb side w/ one-half bar latch
- 1 1/2" x 1/4" inside tie rail
- Double rear doors w/ cam latches & hold backs

CM Trailers reserves the right to make any change in paint, design, or construction as necessary for engineering. All visual representation, specification, and dimensions are based on the latest product information available at the time of publication. Some of the equipment shown or described is available at extra cost. At no time will any of the material or information contained in this publication have any justifications for resolving disputes. All axle ratings will be listed as per FMVSS 120, Section 5.1 states, the maximum load rating of the tires and rims fitted to an axle shall not be less than the GAWR specified on the certification label.