



DAKOTA

STEEL SLANT LOAD BUMPER
PULL HORSE TRAILER.

AVAILABLE SIZES

- 2-horse, 14' x 6' x 6'6" w/2-3500# axles w/1 brake, 15" tires & 6-hole wheels
- 3-horse, 16' x 6' x 6'6" w/2-3500# axles w/1 brake, 15" tires & 6-hole wheels
- 2-horse, 14' x 6' x 7' w/2-3500# axles w/1 brake, 15" tires & 6-hole wheels
- 3-horse, 16' x 6' x 7' w/2-3500# axles w/1 brake, 15" tires & 6-hole wheels
- 2-horse, 14' x 6' 8" x 6'6" w/2-3500# axles w/1 brake, 15" tires & 6-hole wheels
- 3-horse, 16' x 6'8" x 6'6" w/2-5200# axles w/2 brakes, 15" tires & 6-hole wheels
- 2-horse, 14' x 6'8" x 7' w/2-3500# axles w/1 brake, 15" tires & 6-hole wheels
- 3-horse, 16' x 6'8" x 7' w/2-5200# axles w/2 brakes, 15" tires & 6-hole wheels

DIMENSIONS

- 30" tongue length
- 6' or 6'8" width
- 6'6" or 7' Standard height

UNDERCARRIAGE

- Rubber torsion axles w/ four-wheel independent suspension & greasable hubs

COUPLER & JACKS

- 2" Bulldog coupler & safety chains w/hooks (2 5/16" coupler on models with 5200lb axles)
- Emergency breakaway system: switch, cable & battery box compete w/battery & charger
- 7K Top-wind jack w/caster wheel

LIGHTS & ELECTRICAL

- DOT required lighting
- Dome light (1 in stall area)
- Dome lights (1 in tack)

DESIGN FEATURES

- All steel frame w/formed 16 gauge galvalneal side panels, front, and slant wall; **Tongue:** 3"x4" Angle box tongue, **Mainframe:** 2"x3" 3/16" Angle main frame 2"x2" x 3/16" Angle on 24" center crossmember, **Wall:** 1"x2" tube 14 gauge, **Roof:** 1"x1" 16 gauge
- Low profile 6" radius 20 gauge galvalneal roof
- Chrome trim w/ colored vinyl insert
- Round nose
- 16" Tall Aluminum tread plate gravel guard on front & fenders
- Rubber mounted optical window in front
- Plexiglass strap on both sides (plexiglass & rail not standard)
- 2" x 8" Treated wood floor
- Full length 16 gauge galvalneal running boards
- Greasable exterior hinges
- Tag bracket
- Automotive grade 12 step paint process

STALL AREA EQUIPMENT

- Removable 2"x4" slant tubing dividers w/ solid head partition
- Rear Telescoping divider on 6'8" wide mode
- Quick release slam latches on dividers
- Interior tie rings (1 per stall)
- Exterior tie rings (2 per side)
- One-piece rear door w/drop-leg rear gate stop
- Telescoping rear divider on 6'8" wide model

FRONT TACK EQUIPMENT

- Front slant tack room (0' to 4')
- Full height slant partition wall between stalls & front tack room
- 30" Full tack door w/recessed locking handle & hold backs (located on curb side)
- Saddle rack (3 on a tree)
- Clothes rod
- Bridle hooks (6)
- Brush tray

CM Trailers reserves the right to make any change in paint, design, or construction as necessary for engineering. All visual representation, specification, and dimensions are based on the latest product information available at the time of publication. Some of the equipment shown or described is available at extra cost. At no time will any of the material or information contained in this publication have any justifications for resolving disputes. All axle ratings will be listed as per FMVSS 120, Section 5.1 states, the maximum load rating of the tires and rims fitted to an axle shall not be less than the GAWR specified on the certification label.