



## NOMAD GN

ALUMINUM SLANT LOAD GOOSENECK TRAILER W/ SMOOTH ALUMINUM SKIN.

### AVAILABLE SIZES

- 2H 15 x 6'8 x 7' w/4'6" SW w/ 2-5200# axles, 15" tires & 6-hole wheels
- 3H 18 x 6'8 x 7' w/4'6" SW w/ 2-5200# axles, 15" tires & 6-hole wheels
- 4H 21 x 6'8 x 7' w/4'6" SW w/ 2-6000# axles, 16" tires & 8-hole wheels

### DIMENSIONS

- 7' gooseneck length
- 6'8" width
- 7' interior height
- 4'6" short wall

### UNDERCARRIAGE

- Rubber torsion axles w/ four-wheel independent suspension & greasable hubs
- Forward self adjusting electric brakes on all wheels
- Radial tires on silver modular wheels w/ chrome center caps
- Spare tire rack under gooseneck

### COUPLER & JACKS

- Adjustable Stem w/ set screw & pin w/2-5/16" Bulldog Coupler & safety chains w/ hooks
- Emergency breakaway system: switch, cable & battery box compete w/ battery & charger
- 12K Single-speed drop-leg jack w/ removable jack handle/lug wrench

### LIGHTS & ELECTRICAL

- DOT required LED lighting
- Recessed dome lights (1 in each stall area)
- Recessed dome light in tack room

### DESIGN FEATURES

- All aluminum frame w/Smooth aluminum side panels (White aluminum standard)
- Heavy Duty low profile 2"x4" 3/16" steel gooseneck structure
- .125 extruded aluminum top rail
- 1 3/8" x 1 3/8" wall uprights
- 9" extruded aluminum bottom rail
- .040 one-piece aluminum skin roof w/ 1" x 2-1/2" tubing bows on 2' centers
- 30" x 20" Drop down feed doors on head wall
- 24" x 18" Radius sliding windows on butt wall
- Aluminum treadplate on breastplate
- 12" Aluminum plank floor
- Rubber dock bumper below rear door
- Tag bracket
- Graphics package
- Colors available white or black aluminum

### STALL AREA EQUIPMENT

- Adjustable removable slant tubing dividers with head partition

- Telescoping rear divider
- Rotary slam latches on dividers
- Rubber floor mats
- 38" Stalls
- Kick Mats (Butt wall, head wall, slant wall, and rear doors)
- Interior tie rings (2 per stall)
- Exterior tie rings (1 per stall, 3rd on curbside on 3H)
- 50/50 rear doors w/24" x 18" window in each

### FRONT TACK EQUIPMENT

- Front slant tack room (4'6" to 8'6")
- Full height slant partition wall between stalls & front tack room
- 36" Camper door on curbside w/recessed locking handle & window
- Bridle bar (2)
- Rubber Brush Tray
- Blanket bars
- Rubber mats on floor
- Roll-up camper vent including brace for A/C
- Carpet on breast plate and riser deck

CM Trailers reserves the right to make any change in paint, design, or construction as necessary for engineering. All visual representation, specification, and dimensions are based on the latest product information available at the time of publication. Some of the equipment shown or described is available at extra cost. At no time will any of the material or information contained in this publication have any justifications for resolving disputes. All axle ratings will be listed as per FMVSS 120, Section 5.1 states, the maximum load rating of the tires and rims fitted to an axle shall not be less than the GAWR specified on the certification label.